

Product Code	Description
JG8318SUSB2-A	13A 1 Gang Universal Switched Socket Outlet with 2 Port USB Charger (2.1A Max)



JG8318SUSB2-A-WSS



Product back view




Technical Specification

- Socket rated voltage:
250VAC, 50/60Hz
- Socket rated current: 13A*
- USB Charger input supply:
250V 50/60Hz, 0.5A max.
- USB Charger output:
5VDC/2.1A max. (shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size:
2.5mm² - 4mm²
- Dimensions:
95 x 95 x 9.8mm (WxHxD)
- Fix Center: 60.3mm
- Fix Screw: M3.5 x 0.6 x 25mm±
- Mounting box: >40mm depth
 - J1040, flush mounting, plastic
(74.5 x 74.5 x 42mm) (WxHxD)
 - M1050, flush mounting, metal
(75.5 x 64 x 50mm) (WxHxD)
- Comply to Standards:
IEC 62368-1

*For 3-pin BS plug

Applicable on selected type of plugs:

Plug	Description
2-pin Plug (Non-earth)	2.5A, 250V
2-pin Plug (Euro)	2.5A, 250V
2-pin Plug Round	10/16A, 250V
2-pin Plug (Non-earth)	10/16A, 250V
3-pin Plug (BS)	13A, 250V
3-pin Plug Round (BS)	5A, 250V
2-pin Australia Plug	7.5A, 250V
3-pin Australia Plug	10A, 250V
3-pin Australia Plug	15A, 250V
3-pin China Plug	6/10A., 250V
2-pin China Plug	6/10A., 250V

Product Code	Colour
JG8318SUSB2-A-BSS	 Black Interior, Stainless Steel
JG8318SUSB2-A-WSS	 White Interior, Stainless Steel
JG8318SUSB2-A-BLBL	 Black Interior, Matt Black
<i>For other colour, please contact T&J Sales representative</i>	