

Product Code	Description
JC8332LUSB-W	18W Dual QC Fast Charger with Light Module



JC8332LUSB-W-LBL



Product back view

## Technical Specification



- Rated voltage: 100 - 240VAC
- Input current: 0.6A max.
- Output Power: 18W max.
- Output Voltage: 3.6V - 12VDC
- USB ports: 2 USB-A
- Protection:
  - Overload, short-circuit, over-heat protected
- LED indicator: Green
- Recommended wire-size: 0.5 - 2.0mm<sup>2</sup>
- Terminal screw: Galvanized steel
- Terminal buckle: Brass with Nickel

### With Lavina '95 Frame: JC1401

- Dimensions: 95x95x10mm (WxHxD)
- Fix Centre: 60.3 mm
- Fix Screw: M3.5 x 0.6 x 25mm±
- Mounting box: >35mm depth
  - J1040, flush mounting, plastic  
74.5 x 74.5 x 42mm (W x H x D)
  - M1050, flush mounting, metal  
75.5 x 64 x 50mm (W x H x D)
- Comply to Standards:
  - EN 62368-1, IEC 62368-1

Charging Port	Output Voltage (DC)	Output Current (max.)
One USB-A port in use (Supports Quick Charge 2.0 & 3.0)	3.6V...5V	3A
	5.2V...9V	2A
	9.2V...12V	1.5A
Two USB-A ports in use (Standard mode)	5V	2.4A (per port) *
	5V	3.3A (per module) *

\*In compliance to Standards, each port is limited to 2.4A individually, with not more than 3.3A total when both ports are in use.

Product Code	Colour	
JC8332LUSB-W-LWH		Matt White
JC8332LUSB-W-LBL		Matt Black
<i>For other colours, please contact T&amp;J Sales representative</i>		