

Product Code	Description
K8513SUSB2-D	13A 250V Switched BS Socket Outlet & Twin USB Charger (2.1A Max)



K8513SUSB2-D



Product back view

Technical Specification

- Socket rated voltage: 250VAC, 50/60Hz
- Socket rated current: 13A
- USB Charger input supply: 250V 50/60Hz, 0.5A max.
- USB Charger output: 5VDC/2.1A max. (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size: 2.5mm² - 4mm²
- Dimensions: 86 x 86 x 5mm (WxHxD)
- Fix Center: 60.3mm
- Fix Screw: M3.5 x 0.6 x 30mm±
- Mounting box: >35mm depth
 - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)
- Comply to standards:
 - BS1363-2
 - IEC62368-1
 - SS145-2
 - MS589-2
 - EN62368-1

Product Code	Colour
K8513SUSB2-D	 White
K8513SUSB2-SBL-D	 Matt Black (SBL)
K8513SUSB2-MSB-D	 Matt Silver Black (MSB)
<i>For other colour, please contact T&J Sales representative</i>	