

Product Code	Description
K8523SDUSB-DP-D	13A 250V Twin Double Pole Switched BS Socket Outlet & Twin USB Charger (2.1A Max)



K8523SDUSB-DP-D



Product back view

Technical Specification

- Socket rated voltage: 250VAC, 50/60Hz
- Socket rated current: 13A
- USB Output voltage: 5.0VDC
- USB Output current: 2.1A (Shared)
- USB Charger with overload, overheating and short-circuit protection
- Recommended wire size: 2.5mm² - 4mm²
- Double-pole switch (both L & N isolated from load when off)
- Dimensions: 146 x 86 x 5mm (WxHxD)
- Fix Center: 120.6mm
- Fix Screw: M3.5 x 0.6 x 23.5mm±
- Mounting box: >35mm depth
 - M1047D, flush mounting, metal (135 x 75 x 47mm) (WxHxD)
- Comply to standards:
 - BS EN 62368-1
 - BS 1363
 - SS 145-2
 - MS 589-2

Product Code	Colour
K8523SDUSB-DP-D	 White
K8523SDUSB-DP-SBL-D	 Matt Black (SBL)
K8523SDUSB-DP-MSB-D	 Matt Silver Black (MSB)
<i>For other colour, please contact T&J Sales representative</i>	