

Product Code	Description
G8513SUSB2-86	13A 1 Gang Switched BS Socket Outlet with 2 Port USB Charger (2.1A Max)



G8513SUSB2-86-BSFSS



Product back view

## Technical Specification

- Socket rated voltage: 250VAC, 50/60Hz
- Socket rated current: 13A
- USB Charger input supply: 250V 50/60Hz, 0.5A max.
- USB Charger output: 5VDC/2.1A max. (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size: 2.5mm<sup>2</sup> - 4mm<sup>2</sup>
- Dimensions: 86 x 86 x 4 mm (WxHxD)
- Fix Center: 60.3mm
- Fix Screw: M3.5x0.6x30mm±
- Mounting box: > 35mm
  - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
  - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)
- Comply to standards:
  - BS 1363-2
  - MS 589-2
  - IEC 62368
  - EN 62368

Product Code	Colour
G8513SUSB2-86-BFSS	 Black Interior, Stainless Steel, Fingerprint Proof, Satin Nickel
G8513SUSB2-86-BFMR	 Black Interior, Electroplated with Matt Brass, Fingerprint Proof, Satin Brass
G8513SUSB2-86-BSBL	 Black Interior, Matt Black
<i>For other colour, please contact T&amp;J Sales representative</i>	