

Product Code	Description
G8623SDUSB-DP-146	13A 2 Gang DP Switched BS Socket Outlet with 2 Port USB Charger (2.1A Max)



G8623SDUSB-DP-146-BSBL



Product back view

Technical Specification

- Rated voltage: 250VAC, 50/60Hz
- Rated current: 13A
- USB Charger input supply: 250V 50/60Hz, 0.5A max.
- USB Charger output: 5VDC/2.1A max. (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size: 2.5mm² - 4mm²
- Double-pole switch (both "L" & "N" isolated from load when off)
- Dimensions: 146 x 86 x 4 mm (WxHxD)
- Fix Centre: 120.6 mm
- Fix Screw: M3.5x0.6x30mm± x2
M3.5x0.6x25mm± x2
- Mounting box: > 35mm
 - M1047D, flush mounting, metal (135x75x47mm) (WxHxD)
- Comply to standards:
 - BS 1363-2
 - SS 145-2
 - MS 589-2
 - IEC 60950-1/62368-1 (USB Charger)

Product Code	Colour
G8623SDUSB-DP-146-BFSS	 Black Interior, Stainless Steel, Fingerprint Proof, Satin Nickel
G8623SDUSB-DP-146-BFMR	 Black Interior, Electroplated with Matt Brass, Fingerprint Proof, Satin Brass
G8623SDUSB-DP-146-BSBL	 Black Interior, Matt Black
<i>For other colours, please contact T&J Sales representative</i>	