

Product Code	Description
HC8613SUSB2	13A 1 Gang Switched BS Socket Outlet with 2 Port USB Charger (2.1A Max)








HC8613SUSB2-ST5



Product back view

Technical Specification

- Socket rated voltage:
250VAC, 50/60Hz
- Socket rated current: 13A
- USB Charger input supply:
250V 50/60Hz, 0.5A max.
- USB Charger output:
5VDC/2.1A max. (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size:
2.5mm² - 4mm²
- Dimensions: 86 x 86 x 10mm (WxHxD)
- Fix Center: 60.3mm
- Fix Screw: M3.5 x 0.6 x 30mm±
- Mounting box: >35mm depth
 - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)
- Comply to standards:
BS1363-2
IEC62368-1
SS145-2
MS589-2
EN62368-1

Product Code	Colour
HC8613SUSB2	 White
HC8613SUSB2-SBL	 Matt Black (SBL)
HC8613SUSB2-MSB	 Matt Silver Black (MSB)
HC8613SUSB2-PS7	 Dark Champagne (PS7)
HC8613SUSB2-ST5	 Champagne Grey (ST5)
<i>For other colour, please contact T&J Sales representative</i>	

