

Product Code	Description
HC4201HDMI-USB	1 Gang HDMI and USB Socket



HC4201HDMI-USB-SBL



Product back view

Technical Specification

HDMI Connector:

- Female-to-Female connector port
- Operation Voltage: 40VAC max
- Current Rating: 0.5A per contact
- Contact Resistance: 30mΩ max.
- Insulation Resistance: 2000MΩ min.
- Dielectric Withstanding Voltage: 500VAC
- Shield: Brass
- Plating: Nickle
- Contact: Phosphor Bronze
- Contact area: Gold plating
- Solder Tail: Tin plating

- Dimensions: 86 x 86 x 10mm (WxHxD)
- Fix Center: 60.3 mm
- Fix Screw: M3.5 x 0.6 x 30mm±
- Mounting box: >35mm depth*
 - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)
- Comply to standards: GB/T17466.1

USB Connector:

- Female-to-Female connector port
- USB 2.0 Data port feed through

*Allow room for bend radius of HDMI & USB cables

Typical connection method



Top view at the back of product

Product Code	Colour
HC4201HDMI-USB	 White
HC4201HDMI-USB -SBL	 Matt Black (SBL)
HC4201HDMI-USB -MSB	 Matt Silver Black (MSB)
HC4201HDMI-USB -PS7	 Dark Champagne (PS7)
HC4201HDMI-USB -ST5	 Champagne Grey (ST5)
<i>For other colours, please contact T&J Sales representative</i>	

