

Product Code	Description
HC8318SUSBC	16A 1 Gang Universal Switched Socket Outlet with 2 Port USB Charger (2.1A Max, USBA+C)



HC8318SUSBC



Product back view

Technical Specification

- Socket rated voltage: 250VAC, 50/60Hz
- Socket rated current: 13A (with BS plug)
- USB Charger input supply: 250V 50/60Hz, 0.5A max.
- USB Charger output: 5VDC/2.1A max. (USB-A + USB-C Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size: 2.5mm² - 4mm²
- Dimensions: 86x86x10mm (WxHxD)
- Fix Center: 60.3mm
- Fix Screw: M3.5x0.6x30±
- Mounting box: > 35mm
 - R1150, flush mounting, plastic (80x80x48.4 mm) (WxHxD)
 - M1247, flush mounting, metal (79x73x47 mm) (WxHxD)
- Comply to standards: IEC 62368-1

Applicable on selected type of plugs:

Plug Type	Rating
2-pin Plug (Non-earth)	2.5A, 250V
2-pin Plug (Euro)	2.5A, 250V
2-pin Plug Round	10/16A, 250V
2-pin Plug (Non-earth)	10/16A, 250V
3-pin Plug (BS)	13A, 250V
3-pin Plug Round (BS)	5A, 250V
2-pin Australia Plug	7.5A, 250V
3-pin Australia Plug	10A, 250V
3-pin Australia Plug	15A, 250V
3-pin China Plug	6/10A., 250V
2-pin China Plug	6/10A., 250V

Product Code	Colour
HC8318SUSBC	 White
HC8318SUSBC-SBL	 Matt Black (SBL)
HC8318SUSBC-MSB	 Matt Silver Black (MSB)
HC8318SUSBC-PS7	 Dark Champagne (PS7)
HC8318SUSBC-ST5	 Champagne Grey (ST5)
<i>For other colours, please contact T&J Sales representative</i>	

