



Product Code	Description
W8332LUSB	18W 240V QC Twin Type-A USB Charger (Module)



W8332LUSB-LBL



Product back view

Technical Specification

Two Deco module size

Rated voltage: 100 - 240VAC

Input current: 0.6A max.

Output Power: 18W max.

• Output Voltage: 3.6V - 12VDC

• USB ports: 2 USB-A

• Protection:

Overload, short-circuit, over-heat protected

LED indicator: Green

Recommended wire-size: 0.5 - 2.0mm²

Terminal screw: Galvanized steel

Terminal buckle: Brass with Nickel

Dimensions: 45 x 42 x 40 mm (WxHxD)

• Mounting box: >40 mm

R1150, flush mounting, plastic
(80 x 80 x 48.4 mm) (WxHxD)

M1247, flush mounting, metal(79 x 73 x 47 mm) (WxHxD)

Comply to Standards:
EN 62368-1, IEC 62368-1

Charging Port	Output Voltage (DC)	Output Current (max.)
One USB-A port in use	3.6V5V	3A
(Supports Quick Charge 2.0 & 3.0)	5.2V9V	2A
	9.2V12V	1.5A
Two USB-A ports in use	5V	2.4A (per port) *
(Standard mode)	5V	3.3A (per module) *

^{*}In compliance to Standards, each port is limit to 2.4A individually with not more than 3.3A total when both ports are in use.





Product Code	Colour			
W8332LUSB	White			
W8332LUSB-SBL	Matt Black (SBL)			
W8332LUSB-ST	Charcoal Black (ST)			
W8332LUSB-MSB	Matt Silver Black (MSB)			
W8332LUSB-MSL	Matt Silver (MSL)			
For other colours, please contact T&J Sales representative				

Adapter plate for Deco module					
Series	Product Code				
	1 gang adapter plate	2 gang adapter plate	3 gang adapter plate		
deco	W1111	W1112A	W1113		
infinit	HC1231	HC1232			
HARMONY	EA1231	EA1232			
minimalist	EB1231	EB1232			
radiance	K1231-D	K1201-D			
Titanium	GC1231	GC1221			
Ultimate	G1231	G1221			

Adaptor plate for other series is available, please contact T&J Sales representative