

Product Code	Description
EA8613SUSB2	13A 250V Switched BS Socket & Twin USB Charger (2.1A Max)







EA8613SUSB2-MSB



Product back view

## Technical Specification

- Socket rated voltage:  
250VAC, 50/60Hz
- Socket rated current: 13A
- USB Charger input supply:  
250V 50/60Hz, 0.5A max.
- USB Charger output:  
5VDC/2.1A max. (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size:  
2.5mm<sup>2</sup> - 4mm<sup>2</sup>
- Dimensions: 86x86x10mm (WxHxD)
- Fix Center: 60.3 mm
- Fix Screw: M3.5x0.6x23.5±
- Mounting box: >35mm depth
  - R1150, flush mounting, plastic (80x80x48.4mm) (WxHxD)
  - M1247, flush mounting, metal (79x73x47mm) (WxHxD)
- Comply to standards:  
BS1363-2, IEC62368-1,  
SS145-2, MS589-2,  
EN62368-1

Product Code	Colour
EA8613SUSB2	 White
EA8613SUSB2-SBL	 Matt Black (SBL)
EA8613SUSB2-MSB	 Matt Silver Black (MSB)
EA8613SUSB2-MSL	 Matt Silver (MSL)
<i>For other colours, please contact T&amp;J Sales representative</i>	