


Product Code	Description
EA8318SUSB2	16A 250V Universal Socket & Twin USB Charger (2.1A Max)



EA8318SUSB2-RG2




Product back view

Technical Specification

- Rated Voltage: 250V 50/60Hz
- Rated Current: 16A
- USB Charger input supply: 250V, 50/60 Hz. 0.5A max.
- USB Charger Output: 5VDC, 2.1A max (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size: 2.5mm² - 4.0mm²
- Dimensions: 86 x 86 x 10mm (WxHxD)
- Fix Center: 60.3mm
- Fix Screw: M3.5 x 0.6 x 23.5mm±
- Mounting box: >35mm depth
 - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)
- Comply to standards: IEC 62368-1/60950-1 (USB)

USB Charger module

- internally connected within socket



Applicable on selected type of plugs:

Plug	Description
2-pin Plug (Non-earth)	2.5A, 250V
2-pin Plug (Euro)	2.5A, 250V
2-pin Plug Round	10/16A, 250V
2-pin Plug (Non-earth)	10/16A, 250V
3-pin Plug (BS)	13A, 250V
3-pin Plug Round (BS)	5A, 250V
2-pin Australia Plug	7.5A, 250V
3-pin Australia Plug	10A, 250V
3-pin Australia Plug	15A, 250V
3-pin China Plug	6/10A., 250V
2-pin China Plug	6/10A., 250V

Product Code	Colour
EA8318SUSB2	 White
EA8318SUSB2-SBL	 Matt Black (SBL)
EA8318SUSB2-MSB	 Matt Silver Black (MSB)
EA8318SUSB2-MSL	 Matt Silver (MSL)
<i>For other colours, please contact T&J Sales representative</i>	