

Product Code	Description
EB4201HDMI	1 Gang HDMI Socket



EB4201HDMI-MSL



Product back view

Technical Specification

Connector electrical specs.:

- Female-to-Female connector port
- Operation Voltage: 40VAC max
- Current Rating: 0.5A per contact
- Contact Resistance: 30mΩ max.
- Insulation Resistance: 2000MΩ min.
- Dielectric Withstanding Voltage: 500VAC
- Dimensions: 86 x 86 x 10mm (WxHxD)
- Fix Center: 60.3 mm
- Fix Screw: M3.5 x 0.6 x 23.5mm±
- Mounting box: >40mm depth*
 - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)

Connector material specs.:

- Shield: Brass
- Plating: Nickle
- Contact: Phosphor Bronze
- Contact area: Gold plating
- Solder Tail: Tin plating
- Comply to standards: GB/T17466.1

*Allow room for bend radius of HDMI cable

Product Code	Colour
EB4201HDMI	 White
EB4201HDMI-SBL	 Matt Black (SBL)
EB4201HDMI-MSB	 Matt Silver Black (MSB)
EB4201HDMI-MSL	 Matt Silver (MSL)
<i>For other colours, please contact T&J Sales representative</i>	