

Product Code	Description
EB8613SUSB2	13A 250V Switched BS Socket & Twin USB Charger (2.1A Max)



EB8613SUSB2-MSL



Product back view

Technical Specification

- Socket rated voltage:
250VAC, 50/60Hz
- Socket rated current: 13A (BS)
- USB Charger input supply:
250V 50/60Hz, 0.5A max.
- USB Charger output:
5VDC/2.1A max. (Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size:
2.5mm²- 4mm²
- Dimensions: 86x86x10mm (WxHxD)
- Fix Center: 60.3 mm
- Fix Screw: M3.5x0.6x23.5±
- Mounting box: >35mm depth
 - R1150, flush mounting, plastic (80x80x48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79x73x47mm) (WxHxD)
- Comply to standards:
BS1363-2
IEC62368-1
SS145-2
MS589-2
EN62368-1

Product Code	Colour
EB8613SUSB2	 White
EB8613SUSB2-SBL	 Matt Black (SBL)
EB8613SUSB2-MSB	 Matt Silver Black (MSB)
EB8613SUSB2-MSL	 Matt Silver (MSL)
<i>*For other colours, please contact T&J Sales representative</i>	